



Composition:

- Inner tube: polyester elastomer.
- Reinforcement: one or two braids of "aramid" fiber.
- Cover: black pinpricked polyurethane.

Working temperature: From -40° C to +100° C limited to +70° C for air and water based fluids.

Part nº	DN	Ø in	Ø out	Working Pressure (bar)	Working pressure (psi)	Burst pressure (bar)	Burst pressure (psi)	Bending radius (mm)	Weight (kg/m)
MTR08003	3/16"	5	8,9	350	5.000	1.400	20.000	30	0,050
MTR08004	1/4"	6,5	11,5	350	5.000	1.400	20.000	50	0,085
MT08005	5/16"	8,1	13,4	300	4.300	1.200	17.200	55	0,105
MTR08005	5/16"	8,1	13,4	300	4.300	1.200	17.200	55	0,105
MTR08006	3/8"	9,7	15,5	280	4.000	1.120	16.000	60	0,135
MT08008	1/2"	13	19,9	245	3.500	980	14.000	80	0,200
MTR08008	1/2"	13	19,9	245	3.500	980	14.000	80	0,200
MT08010	5/8"	16,3	23,4	200	2.900	800	11.600	125	0,250
MTR08010	5/8"	16,3	23,4	200	2.900	800	11.600	125	0,250
MTR08012	3/4"	19,5	26,9	165	2.300	660	9.200	150	0,320
MTR08016	1"	25,9	34,2	140	2.000	560	8.000	200	0,440