



Composition:

- Inner tube: special synthetic rubber resistant to hydraulic oil.
- Reinforcement: one textile braid + one braid of steel wire.
- Cover: textil braid impregnated with synthetic rubber resistant to oil and weather.

Working temperature From -40° C to +100° C.

Part n°	DN	Ø in	Ø out	Working Pressure (bar)	Working pressure (psi)	Burst pressure (bar)	Burst pressure (psi)	Bending radius (mm)	Weight (kg/m)
M250305	1/4"	6,4	14,3	207	3.002	828	12.006	86	0,296
M250308	13/32"	10,3	19,5	138	2.001	552	8.004	117	0,408
M250310	1/2"	12,7	23,4	121	1.755	484	7.018	140	0,567
M250312	5/8"	15,9	26,8	103	1.494	412	5.974	165	0,698
M250324	1"3/8	34,9	43,7	34	493	136	1.972	267	1,134
M250332	1"13/16	46	56,4	24	348	96	1.392	337	1,351
MDD250304	3/16"	4,8	13,2	207	3.002	828	12.006	76	0,263
MDD250305	1/4"	6,4	14,3	207	3.002	828	12.006	86	0,296
MDD250306	5/16	7,9	16,7	155	2.248	620	8.990	102	0,363
MDD250308	13/32"	10,3	19,5	138	2.001	552	8.004	117	0,408
MDD250310	1/2"	12,7	23,4	121	1.755	484	7.018	140	0,567
MDD250312	5/8"	15,9	26,8	103	1.494	412	5.974	165	0,698
MDD250316	7/8"	22,2	30,6	55	798	220	3.190	187	0,741
MDD250320	1"1/8	28,6	37,3	43	624	172	2.494	229	0,975
MDD250324	1"3/8"	34,9	43,7	34	493	136	1.972	267	1,134
MDD250332	1"13/16	46	56,4	24	348	96	1.392	337	1,351