



Straight male stud coupling with captive seal BSP cyl

1/2



Part nº	ØD1	Serie	R1	Working Pressure (bar)	L	L1	L2	HEX 1
STA AL 6 R 1/8 WD	6	L	1/8" BSP	500	23,5	8	8,5	14
STA AL 6 R 1/4 WD	6	L	1/4" BSP	500	28	12	9	19
STA AL 6 R 3/8 WD	6	L	3/8 BSP	500	31,5	12	12,5	22
STA AL 8 R 1/8 WD	8	L	1/8" BSP	500	24,5	8	9,5	14
STA AL 8 R 1/4 WD	8	L	1/4" BSP	500	29	12	10	19
STA AL 8 R 3/8 WD	8	L	3/8 BSP	400	29,5	12	10,5	22
STA AL 8 R 1/2 WD	8	L	1/2" BSP	400	34	14	13	27
STA AL 10 R 1/8 WD	10	L	1/8" BSP	500	25,5	8	10,5	17
STA AL 10 R 1/4 WD	10	L	1/4 BSP	500	30	12	11	19
STA AL 10 R 3/8 WD	10	L	3/8 BSP	400	30,5	12	11,5	22
STA AL 10 R 1/2 WD	10	L	1/2 BSP	400	33	14	12	27
STA AL 12 R 1/4 WD	12	L	1/4 BSP	400	31	12	12	19
STA AL 12 R 3/8 WD	12	L	3/8 BSP	400	31,5	12	12,5	22
STA AL 12 R 1/2 WD	12	L	1/2 BSP	400	34	14	13	27
STA AL 12 R 3/4 WD	12	L	3/4" BSP	400	40,5	16	16,5	41
STA AL 15 R 3/8 WD	15	L	3/8 BSP	400	32,5	12	13,5	24
STA AL 15 R 1/2 WD	15	L	1/2 BSP	315	35	14	14	27
STA AL 15 R 3/4 WD	15	L	3/4 BSP	250	37	16	14	32
STA AL 18 R 3/8 WD	18	L	3/8" BSP	400	33,5	12	11,5	27
STA AL 18 R 1/2 WD	18	L	1/2 BSP	400	36	14	14,5	27
STA AL 18 R 3/4 WD	18	L	3/4 BSP	250	38	16	14,5	32
STA AL 22 R 1/2 WD	22	L	1/2 BSP	250	38	14	16,5	32
STA AL 22 R 3/4 WD	22	L	3/4 BSP	250	40	16	16,5	32
STA AL 22 R 1 WD	22	L	1	250	42	18	16,5	41
STA AL 28 R 3/4 WD	28	L	3/4 BSP	250	41	16	17,5	41
STA AL 28 R 1 WD	28	L	1" BSP	250	43	18	17,5	41
STA AL 28 R 1 1/4 WD	28	L	1" 1/4 BSP	250	46	20	18,5	50

**Straight male stud coupling with captive seal BSP
cyl****2/2**

Part n°	ØD1	Serie	R1	Working Pressure (bar)	L	L1	L2	HEX 1
STA AL 35 R 1 WD	35	L	1" BSP	250	45,5	18	17,5	46
STA AL 35 R 1 1/4 WD	35	L	1 1/4 BSP	250	48	20	17,5	50
STA AL 42 R 1 1/2 WD	42	L	1 1/2 BSP	250	52	22	19	55
STA AS 6 R 1/4 WD	6	S	1/4 BSP	630	32	12	13	19
STA AS 8 R 1/4 WD	8	S	1/4 BSP	630	34	12	15	19
STA AS 8 R 3/8 WD	8	S	3/8 BSP	630	34,5	12	15,5	22
STA AS 10 R 1/4 WD	10	S	1/4 BSP	630	34	12	14,5	19
STA AS 10 R 3/8 WD	10	S	3/8 BSP	630	34,5	12	15	22
STA AS 10 R 1/2 WD	10	S	1/2 BSP	630	37	14	15,5	27
STA AS 12 R 1/4 WD	12	S	1/4 BSP	630	36	12	16,5	22
STA AS 12 R 3/8 WD	12	S	3/8 BSP	630	36,5	12	17	22
STA AS 12 R 1/2 WD	12	S	1/2 BSP	630	39	14	17,5	27
STA AS 14 R 3/8 WD	14	S	3/8" BSP	630	38,5	12	12,5	24
STA AS 14 R 1/2 WD	14	S	1/2 BSP	630	41	14	19	27
STA AS 16 R 3/8 WD	16	S	3/8 BSP	420	38,5	12	18	27
STA AS 16 R 1/2 WD	16	S	1/2 BSP	420	41	14	18,5	27
STA AS 16 R 3/4 WD	16	S	3/4 BSP	420	43	16	18,5	32
STA AS 20 R 1/2 WD	20	S	1/2" BSP	420	45	14	12	32
STA AS 20 R 3/4 WD	20	S	3/4 BSP	420	47	16	20,5	32
STA AS 25 R 3/4 WD	25	S	3/4 BSP	420	51	16	23	41
STA AS 25 R 1 WD	25	S	1"BSP	420	53	18	23	41
STA AS 30 R 1 WD	30	S	1" BSP	420	55	18	23,5	46
STA AS 30 R 1 1/4 WD	30	S	1 1/4 BSP	420	57	20	23,5	50
STA AS 38 R 1 1/4 WD	38	S	1" 1/4 BSP	315	62	20	26	55
STA AS 38 R 1 1/2 WD	38	S	1 1/2 BSP	315	64	22	24	55