


ISO 7241-A Quick release coupling free flow BSP

Mild Steel

1/1**Material:** Steel**Seals:** NBR**Working temperature:** -25°C / +100°C**Working pressure:** 250-350 bar

Part nº	R1	Working Pressure (bar)	ISO size	BG size	Coupling	Water flow(l/min)	FLOW MAX (l/min)	L	L1	L2	HEX 1	HEX 2	ØE	A
A831104	1/4" BSP	350	6,3	1	M	12	24	70,5		35		19		11,8
A831106	3/8" BSP	350	10	2	M	23	46	85,5		42,5		22		17,3
A831108	1/2" BSP	300	12,5	3	M	45	90	96,5		48		27		20,5
A831112	3/4" BSP	250	20	4	M	106	220	114,5		57		34		29,1
A831116	1" BSP	250	25	5	M	189	380	135,5		67,5		41		34,3
A831120	1"1/4 BSP	250	31,5	6	M	288	580	150,6		75		50		45
A831204	1/4" BSP	350	6,3	1	H	12	24	70,5	49,2		19		26	11,6
A831206	3/8" BSP	350	10	2	H	23	46	85,5	60,5		22		30	17,3
A831208	1/2" BSP	300	12,5	3	H	45	90	96,5	70		27		38	20,5
A831212	3/4" BSP	250	20	4	H	106	220	114,5	84,3		34		45	29,1
A831216	1" BSP	250	25	5	H	189	380	135,5	101		41		52	34,3
A831220	1"1/4 BSP	250	31,5	6	H	288	580	150,6	117		50		70	