




Flow dividers with anti shock valves, group 1



*Flow for body

Group 1: inlet 1/2", outlet 3/8"

Minimum pressure: Up to 3.4 cc: 80 bar; all others: 50 bar

Sewer system M12x1.5

Flow accuracy ± 3 %

anti-shock valve: 200 bar

Part n°	*Min. flow (l/min)	*Max. flow (l/min)	Max. Press. (bar)	cm ³ /body	N° bodies
DE116X2	1,36	5.1	240	1.6	2
DE116X4	1,36	5.1	240	1.6	4
DE121X2	1,6	6.0	240	2.1	2
DE121X4	1,6	6.0	240	2.1	4
DE131X2	2,4	9.0	240	3.1	2
DE131X4	2,4	9.0	240	3.1	4
DE142X2	3,28	12.3	240	4.2	2
DE142X4	3,28	12.3	240	4.2	4
DE152X2	4,08	15.3	240	5.2	2
DE152X4	4,08	15.3	240	5.2	4
DE163X2	4,88	18.3	240	6.3	2
DE163X4	4,88	18.3	240	6.3	4
DE174X2	5,68	21.3	240	7.4	2
DE174X4	5,68	21.3	240	7.4	4
DE184X2	6,4	24.0	240	8.4	2



Gear flow dividers

Gear Flow divider without valves

Flow dividers with anti shock valves, group 1

Page: 2/2

Part n°	*Min. flow (l/min)	*Max. flow (l/min)	Max. Press. (bar)	cm ³ /body	N° bodies
DE184X4	6,4	24.0	240	8.4	4

*** Review attached PDF***