

Rigid pipe - 6 mts

Stainless Steel AISI 316-L

1/2**Specifications:** Austenitic S.S. Seamless Tube. Heat treatment of Annealing.**Standards:** EN 10305-4, ASTM-A 269 / A 213**Dimensions:** According to EN 10305-4:2003 norm tolerances**Safety factor:** 4:1**Finishing:** polished at 240 grit belt

Remark: Note: The post-manufacturing cleaning process: pickling, acid flow, water jetting, pressure and blowing does not ensure the total absence of remains or dirt
For more demanding applications, ask us about our PREMIUM stainless steel tubes

Part n°	Ø outer	Ø in	WP (bar)	Thickness (mm)	Weight (kg/m)	L
ZTH0060100	6	4	490	1	0,125	- 6 MTS
ZTH0060150	6	3	735	1,5	0,169	- 6 MTS
ZTH0080100	8	6	368	1	0,175	- 6 MTS
ZTH0080150	8	5	551	1,5	0,244	- 6 MTS
ZTH0100100	10	8	294	1	0,225	- 6 MTS
ZTH0100150	10	7	441	1,5	0,318	- 6 MTS
ZTH0100200	10	6	588	2	0,401	- 6 MTS
ZTH0120100	12	10	245	1	0,275	- 6 MTS
ZTH0120150	12	9	368	1,5	0,393	- 6 MTS
ZTH0120200	12	8	490	2	0,501	- 6 MTS
ZTH0120250	12	7	610	2,5	0,585	- 6 MTS
ZTH0140200	14	10	420	2	0,600	- 6 MTS
ZTH0150150	15	12	294	1,5	0,506	- 6 MTS
ZTH0160200	16	12	368	2	0,700	- 6 MTS
ZTH0160300	16	10	551	3	0,977	- 6 MTS
ZTH0180150	18	15	245	1,5	0,618	- 6 MTS
ZTH0180200	18	14	327	2	0,800	- 6 MTS
ZTH0200300	20	14	441	3	1,275	- 6 MTS
ZTH0220200	22	18	267	2	1,000	- 6 MTS
ZTH0250250	25	20	294	2,5	1,408	- 6 MTS
ZTH0250300	25	19	353	3	1,650	- 6 MTS
ZTH0280200	28	24	210	2	1,302	- 6 MTS
ZTH0300300	30	24	294	3	2,028	- 6 MTS
ZTH0350200	35	31	168	2	1,653	- 6 MTS
ZTH0380400	38	30	309	4	3,355	- 6 MTS
ZTH0420200	42	38	140	2	2,003	- 6 MTS
ZTH0420300	42	36	210	3	2,930	- 6 MTS

Rigid pipe - 6 mts

Stainless Steel AISI 316-L

2/2

Part n°	Ø outer	Ø in	WP (bar)	Thickness (mm)	Weight (kg/m)	L
---------	---------	------	----------	----------------	---------------	---

Pipes are supplied in commercial lengths of 6 m (± 100 mm)