

Rigid pipe - 3 mts

Stainless Steel AISI 316-L

1/2**Specifications:** Austenitic S.S. Seamless Tube. Heat treatment of Annealing.**Standards:** EN 10305-4, ASTM-A 269 / A 213**Dimensions:** According to EN 10305-4:2003 norm tolerances**Finishing:** polished at 240 grit belt

Remark: Note: The post-manufacturing cleaning process: pickling, acid flow, water jetting, pressure and blowing does not ensure the total absence of remains or dirt
For more demanding applications, ask us about our PREMIUM stainless steel tubes

Part nº	Ø outer	Ø in	WP (bar)	Thickness (mm)	Weight (kg/m)	L
ZTH0060100-3	6	4	490	1	0,125	- 3 MTS
ZTH0060150-3	6	3	735	1.5	0.169	- 3 MTS
ZTH0080100-3	8	6	368	1	0,175	- 3 MTS
ZTH0080150-3	8	5	551	1.5	0.244	- 3 MTS
ZTH0100100-3	10	8	294	1	0.225	- 3 MTS
ZTH0100150-3	10	7	441	1,5	0,318	- 3 MTS
ZTH0120100-3	12	10	245	1	0,275	- 3 MTS
ZTH0100200-3	10	6	588	2	0.401	- 3 MTS
ZTH0120150-3	12	9	368	1,5	0,393	- 3 MTS
ZTH0120200-3	12	8	490	2	0.501	- 3 MTS
ZTH0120250-3	12	7	610	2,5	0.585	- 3 MTS
ZTH0140200-3	14	10	420	2	0,600	- 3 MTS
ZTH0150150-3	15	12	294	1,5	0,506	- 3 MTS
ZTH0160200-3	16	12	368	2	0,700	- 3 MTS
ZTH0160300-3	16	10	551	3	0,977	- 3 MTS
ZTH0180150-3	18	15	245	1,5	0,618	- 3 MTS
ZTH0180200-3	18	14	327	2	0,800	- 3 MTS
ZTH0200300-3	20	14	441	3	1,275	- 3 MTS
ZTH0220200-3	22	18	267	2	1,000	- 3 MTS
ZTH0250250-3	25	20	294	2,5	1,408	- 3 MTS
ZTH0250300-3	25	19	353	3	1,650	- 3 MTS
ZTH0280200-3	28	24	210	2	1,302	- 3 MTS
ZTH0300300-3	30	24	294	3	2,028	- 3 MTS
ZTH0350200-3	35	31	168	2	1,653	- 3 MTS
ZTH0380400-3	38	30	309	4	3,355	- 3 MTS
ZTH0420200-3	42	38	140	2	2,003	- 3 MTS
ZTH0420300-3	42	36	210	3	2,930	- 3 MTS

Rigid pipe - 3 mts

Stainless Steel AISI 316-L

2/2

Part nº	Ø outer	Ø in	WP (bar)	Thickness (mm)	Weight (kg/m)	L
---------	---------	------	----------	----------------	---------------	---

Pipes are supplied in commercial lengths of 3 m (± 100 mm)