


Quick couplings 7241-A NPT TrAle

Stainless Steel AISI 316-L

1/1**Material:** Stainless Steel**Seals:** FKM + PTFE**Working temperature:** -20°C / +180°C

Part n°	R1	Working Pressure (bar)	ISO size	BG size	Coupling	Water flow(l/min)	L	L1	L2	HEX 1	HEX 2	ØD
ZB801104	1/4" NPT	250	6,3	1	M	12	71	50	-	19	-	*
ZB801106	3/8" NPT	250	10	2	M	23	75	56	-	22	-	*
ZB801108	1/2" NPT	250	12,5	3	M	45	88	66	-	27	-	*
ZB801112	3/4" NPT	250	20	4	M	106	110	80	-	34	-	*
ZB801116	1" NPT	200	25	5	M	189	119,5	94	-	41	-	*
ZB801204	1/4" NPT	250	6,3	1	H	12	71	-	35,5	-	19	*
ZB801206	3/8" NPT	250	10	2	H	23	75	-	36,5	-	22	*
ZB801208	1/2" NPT	250	12,5	3	H	45	88	-	43,5	-	27	*
ZB801212	3/4" NPT	250	20	4	H	106	110	-	57	-	35	*
ZB801216	1" NPT	200	25	5	H	189	119,5	-	59,5	-	41	*