

Air conditioning DAYCO M520008

Documentation publisher / supplier: DICSA

Manufacturer part number / published order designation: M520008

Published model: M520008

About this compilation

Prepared by Hydmaster from selected manufacturer documentation. Original technical pages follow without cropped drawings, rewritten data or altered units. This cover and index are Hydmaster editorial material, not a manufacturer-issued exact-execution datasheet.

Coverage: selected pages relevant to the identified size and configuration. Other options or neighbouring models retained on an original page apply only where explicitly identified.

Execution notes and conditions

The excerpt preserves the currently linked technical catalogue edition; differently coded newer product-card variants are not treated as equivalent.

Rows and illustrations for other sizes retained on the same original page are not assigned to this article.

Source-page index

Source page numbers below are physical pages of each complete original PDF. The original printed page labels and technical content remain unchanged. Compiled page numbers count this cover/index.

Source A: DICSA Hydraulic Hoses - Technical Catalogue

Original pages	Compiled pages	Relevant content
152	2	Exact M520008 row with the family construction, application, composition, size and stated pressure/temperature/geometry conditions. Refrigerant applicability is specifically R12/R134A, not every refrigerant.

Aire acondicionado. Freón barrier

Air conditioning. Freon barrier
Climatisation. Freon barrier



-30°C → +95°C



SAE J51
SAE J2064

INDUS TrAie®

COMPOSICIÓN • COMPOSITION • COMPOSITION



// Nitrilo, Nylon y Neopreno // Nitrile, Nylon and Neoprene // Nitrile, Nylon et Neoprene



1 // Malla textil // Textile braid // Tresse Textile



// EPDM // EPDM // EPDM



	DN	mm	mm	bar	psi	bar	psi	mm	kg/m
M520006	5/16	7,9	19	24	350	138	2000	101,6	0,272
M520008	13/32	10,3	23,1	24	350	138	2000	119,4	0,291
M520010	1/2	12,7	25,4	24	350	138	2000	139,7	0,449
M520012	5/8	15,9	28,7	24	350	121	1750	165,1	0,069



Válido para:
Sistemas con refrigerante
R12 y R134A

Used For:
R12 and R134A
refrigerant systems only

Utilisée pour:
Systèmes avec réfrigérants
R12 et R134A

