Milk hose anti-extrusion polyamide spiral 10 bar MI020510076

Documentation publisher / supplier: DICSA

Manufacturer part number / published order designation: MI020510076

Published model: MI020510076

About this compilation

Prepared by Hydmaster from selected manufacturer documentation. Original technical pages follow without cropped drawings, rewritten data or altered units. This cover and index are Hydmaster editorial material, not a manufacturer-issued exact-execution datasheet.

Coverage: selected pages relevant to the identified size and configuration. Other options or neighbouring models retained on an original page apply only where explicitly identified.

Execution notes and conditions

The excerpt preserves the currently linked technical catalogue edition; differently coded newer product-card variants are not treated as equivalent.

Rows and illustrations for other sizes retained on the same original page are not assigned to this article.

Source-page index

Source page numbers below are physical pages of each complete original PDF. The original printed page labels and technical content remain unchanged. Compiled page numbers count this cover/index.

Source A: DICSA Hydraulic Hoses - Technical Catalogue

Original pages	Compiled pages	Relevant content
147	2	Exact MI020510076 row with the family construction, application, composition, size and stated pressure/temperature/geometry conditions. Cleaning condition is unpressurised, below130°C for maximum30minutes, not the operating temperature.

Leche anti-extrusión espiral poliamida 10 bar

Milk hose anti- extrusion polyamide spiral 10 bar
Tuyau à lait anti-extrusion spirale polyamide 10 bar

INDUS TrAle®

-35°C → +80°C

3, 15: 1

BfR XX1: 2002 (Kat. 2)

FDA

COMPOSICIÓN · COMPOSITION · COMPOSITION

// **NR blanco liso** // NR, white, smooth // NR, blanc, lisse

// **Mallas textiles enrolladas** // Textile wrapped braids // Tresses textiles enroulées

// **Hilo plástico helicoidal** // Plastic helix // Hélice en plastique

// **NR azul** // NR Blue // NR Bleu

// **Sin presión < 130ºC , max. 30 min** // Unpressurised < 130ºC max. 30 min // Sans pression < 130 ºC, max. 30 min

	mm	mm	bar	psi	bar	psi	mm	kg/m
MI020510025	25	38	10	145	31,5	455	67	0,94
MI020510032	32	45	10	145	31,5	455	86	1,14
MI020510038	38	52	10	145	31,5	455	105	1,36
MI020510051	51	66	10	145	31,5	455	250	2,23
MI020510063	63	78	10	145	31,5	455	350	2,51
MI020510076	76	93	10	145	31,5	455	450	3,19