Alcoholic beverages max. 40% FDA 10 bar MI020610051

Documentation publisher / supplier: DICSA

Manufacturer part number / published order designation: MI020610051

Published model: MI020610051

About this compilation

Prepared by Hydmaster from selected manufacturer documentation. Original technical pages follow without cropped drawings, rewritten data or altered units. This cover and index are Hydmaster editorial material, not a manufacturer-issued exact-execution datasheet.

Coverage: selected pages relevant to the identified size and configuration. Other options or neighbouring models retained on an original page apply only where explicitly identified.

Execution notes and conditions

The excerpt preserves the currently linked technical catalogue edition; differently coded newer product-card variants are not treated as equivalent.

Rows and illustrations for other sizes retained on the same original page are not assigned to this article.

Source-page index

Source page numbers below are physical pages of each complete original PDF. The original printed page labels and technical content remain unchanged. Compiled page numbers count this cover/index.

Source A: DICSA Hydraulic Hoses - Technical Catalogue

Original pages	Compiled pages	Relevant content
148	2	Exact MI020610051 row with the family construction, application, composition, size and stated pressure/temperature/geometry conditions. Cleaning condition is unpressurised, below130°C for maximum30minutes, not the operating temperature.

Bebidas alcohólicas max. 40% 10 bar

Alcoholic beverages max. 40% FDA 10 bar
Boissons alcoolisées max.40 % FDA 10 bar

INDUS TrAle®

-35°C → +95°C

3,15 : 1

BfR XX1: 2002 (Kat. 2)

FDA

COMPOSICIÓN · COMPOSITION · COMPOSITION

//**EPDM blanco liso** // EPDM white, smooth // EPDM blanc lisse

// **Mallas textiles enrolladas** // Textile wrapped // Textiles enroulées

// **Espiral metálica galvanizada**// Galvanized metallic spiral braid // Spirale métallique galvanisée

// **SBR/NR/EPDM roja** // SBR/NR/EPDM, red // SBR/NR/EPDM rouge

// **Sin presión < 130ºC , max. 30 min** // Unpressurised < 130ºC max. 30 min // Sans pression < 130 ºC, max. 30 min

	mm	mm	bar	psi	bar	psi	mm	kg/m
MI020610025	25	37	10	145	31,5	455	110	0,95
MI020610038	38	50	10	145	31,5	455	180	1,37
MI020610051	51	63	10	145	31,5	455	250	2,02
MI020610076	76	88	10	145	31,5	455	450	3,39