Sandblast hose - impulsion 12 bar MI030112025

Documentation publisher / supplier: DICSA

Manufacturer part number / published order designation: MI030112025

Published model: MI030112025

About this compilation

Prepared by Hydmaster from selected manufacturer documentation. Original technical pages follow without cropped drawings, rewritten data or altered units. This cover and index are Hydmaster editorial material, not a manufacturer-issued exact-execution datasheet.

Coverage: selected pages relevant to the identified size and configuration. Other options or neighbouring models retained on an original page apply only where explicitly identified.

Execution notes and conditions

The excerpt preserves the currently linked technical catalogue edition; differently coded newer product-card variants are not treated as equivalent.

Rows and illustrations for other sizes retained on the same original page are not assigned to this article.

Source-page index

Source page numbers below are physical pages of each complete original PDF. The original printed page labels and technical content remain unchanged. Compiled page numbers count this cover/index.

Source A: DICSA Hydraulic Hoses - Technical Catalogue

Original pages	Compiled pages	Relevant content
142	2	Exact MI030112025 row with the family construction, application, composition, size and stated pressure/temperature/geometry conditions.

Chorro de arena - impulsión 12 bar

Sandblast hose- delivery 12 bar
Tuyau sablage- refoulement 12 bar

INDUS TrAle®

-35°C → +80°C

3,15 : 1

COMPOSICIÓN · COMPOSITION · COMPOSITION

// **NR/SBR/BR liso negro antiestático** // Antistatic NR/ SBR/NP, black, smooth// NR/ SBR/NP antistatique lisse noir

// **Mallas textiles enrolladas** // Textile wrapped // Textiles enroulées

// **SBR antiestático negro** // Antistatic SBR black // SBR antistatique noir

	mm	mm	bar	psi	bar	psi	mm	kg/m
MI030112013	13	27	12	175	38	550	130	0,50
MI030112019	19	33	12	175	38	550	190	0,65
MI030112025	25	39	12	175	38	550	250	0,80
MI030112032	32	48	12	175	38	550	320	1,10
MI030112038	38	54	12	175	38	550	380	1,35
MI030112042	42	56	12	175	38	550	420	1,26