EN857 2SNK hose TrAle Gold - HighPressure MS2SNK12

Documentation publisher / supplier: DICSA

Manufacturer part number / published order designation: MS2SNK12

Published model: MS2SNK12

About this compilation

Prepared by Hydmaster from selected manufacturer documentation. Original technical pages follow without cropped drawings, rewritten data or altered units. This cover and index are Hydmaster editorial material, not a manufacturer-issued exact-execution datasheet.

Coverage: selected pages relevant to the identified size and configuration. Other options or neighbouring models retained on an original page apply only where explicitly identified.

Execution notes and conditions

The excerpt preserves the currently linked technical catalogue edition; differently coded newer product-card variants are not treated as equivalent.

Rows and illustrations for other sizes retained on the same original page are not assigned to this article.

Source-page index

Source page numbers below are physical pages of each complete original PDF. The original printed page labels and technical content remain unchanged. Compiled page numbers count this cover/index.

Source A: DICSA Hydraulic Hoses - Technical Catalogue

Original pages	Compiled pages	Relevant content
40	2	Exact MS2SNK12 row with the family construction, application, composition, size and stated pressure/temperature/geometry conditions.

ROCKCOVER

HIGH PRESSURE

FLEXLINE

2SNK

TrΔle® GOLD HighPressure

-40°C → 100°C

4 : 1

COMPOSICIÓN · COMPOSITION · COMPOSITION

// **Caucho sintético** // Synthetic rubber // Caoutchouc synthétique

2 // **Mallas metálicas** // Steel wire braids // Tresses métalliques

// **Caucho sintético** // Synthetic rubber // Caoutchouc synthétique

	DN	mm	mm	bar	psi	bar	psi	mm	kg/m
MS2SNK04	1/4"	6,6	13,4	450	6525	1800	26107	45	0,27
MS2SNK05	5/16"	8,3	15,0	420	6090	1680	24366	60	0,31
MS2SNK06	3/8"	9,9	17,0	385	5585	1540	22336	70	0,39
MS2SNK08	1/2"	13,0	20,7	345	5000	1380	20015	90	0,52
MS2SNK10	5/8"	16,4	23,6	290	4205	1160	16824	130	0,651
MS2SNK12	3/4"	19,5	27,7	280	4060	1120	16244	160	0,79
MS2SNK16	1"	26,0	35,6	200	2900	800	11603	210	1,15
*	1-1/4"	32,5	43,5	175	2540	700	10153	300	1,57

// ***Bajo consulta** // On request // Sur demande