EN 856 4SH Hose MW456912

Documentation publisher / supplier: DICSA

Manufacturer part number / published order designation: MW456912

Published model: MW456912

About this compilation

Prepared by Hydmaster from selected manufacturer documentation. Original technical pages follow without cropped drawings, rewritten data or altered units. This cover and index are Hydmaster editorial material, not a manufacturer-issued exact-execution datasheet.

Coverage: selected pages relevant to the identified size and configuration. Other options or neighbouring models retained on an original page apply only where explicitly identified.

Execution notes and conditions

The excerpt preserves the currently linked technical catalogue edition; differently coded newer product-card variants are not treated as equivalent.

Rows and illustrations for other sizes retained on the same original page are not assigned to this article.

Source-page index

Source page numbers below are physical pages of each complete original PDF. The original printed page labels and technical content remain unchanged. Compiled page numbers count this cover/index.

Source A: DICSA Hydraulic Hoses - Technical Catalogue

Original pages	Compiled pages	Relevant content
79	2	Exact MW456912 row with the family construction, application, composition, size and stated pressure/temperature/geometry conditions.

EN 856 4SH

ΔMW - GreenLine

-40°C → +100°C

COMPOSICIÓN · COMPOSITION · COMPOSITION

// **Caucho sintético** // Synthetic rubber // Caoutchouc synthétique

4 // **Mallas metálicas** //Steel wire braids // Tresses métalliques

// **Goma sintética** // Synthetic rubber // Caoutchouc synthétique

	DN	mm	mm	bar	psi	bar	psi	mm	kg/m
MW456912	3/4"	19	31,5	420	6090	1680	24360	280	1,7
MW456916	1"	25,2	38,5	380	5510	1520	22040	340	2,5
MW456920	1"1/4	32,2	45,2	325	4712	1300	18850	460	3
*	1"1/2	38,5	53,5	290	4206	1160	16824	560	3,6
*	2"	51,2	68,1	250	3625	1000	14504	700	5

// ***Bajo consulta** // On request // Sur demande