Electric motors three-phase with flange (B5)

Part nº	Details	Voltage (V)	Shaft	Ø Flange (mm)	R.P.M.	POWER (HP)
MET0.25B5	IE1	230/400 V (50/60Hz)	11	140	1500	0,25
MET0.33B5	IE1	230/400 V (50/60Hz)	14	160	1500	0,33
MET0.5B5	IE1	230/400 V (50/60Hz)	14	160	1500	0,5
MET0.75B5	IE1	230/400 V (50/60Hz)	19	200	1500	0,75
MET1B5	IE3	230/400 V (50/60Hz)	19	200	1500	1
MET1.5B5	IE3	230/400 V (50/60Hz)	24	200	1500	1,5
MET2B5	IE3	230/400 V (50/60Hz)	24	200	1500	2
MET3B5	IE3	230/400 V (50/60Hz)	28	250	1500	3
MET4B5	IE3	230/400 V (50/60Hz)	28	250	1500	4
MET5.5B5	IE3	230/400 V (50/60Hz)	28	250	1500	5,5
MET7.5B5	IE3	400/690 V	38	300	1500	7,5
MET10B5	IE3	400/690 V	38	300	1500	10
MET15B5	IE3	400/690 V	42	350	1500	15
MET20B5	IE3	400/690 V	42	350	1500	20
MET30B5	IE3	400/690 V	48	350	1500	30
MET40B5	IE3	400/690 V	55	400	1500	40
MET50B5	IE3	400/690 V	60	450	1500	50
MET60B5	IE3	400/690 V	60	450	1500	60
MET75B5	IE3	400/690 V	65	550	1500	75

The information gathered in this technical documentation (Catalogue) has an informative character and can be modified without previous notice. DICSA will not accept any type of responsibility resulting from an inappropriate use of the product, except the ones related to manufacturing defects.