

BDC COUNTERBALANCE SAE


DOUBLE COUNTERBALANCE VALVES FOR CLOSED CENTER

BDC counterbalance valves are used to keep a load locked, the built-in relief valve protects the system from overpressure in the cylinder by draining the oil.



HYDRAULIC CIRCUIT






mm [Inches]


TECHNICAL CHARACTERISTICS

mm [Inches]

F	H	C	L	S	R	ØE
SAE6 [9/16-18 UNF]	50 [1.97]	23 [0,91]	127 [5]	6 [0,24]	44 [1,75]	8,2 [0,32]
SAE8 [3/4-16 UNF]						
SAE10 [7/8-16 UNF]	60 [2,36]	21 [0,83]	129 [5,08]	8,5 [0,33]	51,5 [2,03]	8,5 [0,33]
Steel body (on request aluminium body)						

PERFORMANCES





ORDERING CODE

CODE	TYPE	F ports	MAX FLOW l/min [USgpm]	MAX PRESSURE bar [PSI]	STANDARD SETTING bar [PSI]	RANGE SPRING bar [PSI]	INCREASE TO TURN bar [PSI]	PILOT RATIO	WEIGHT kg [lb]
FA2047	BDC1S21	SAE6	30 [7,9]	350 [5075]	210 [3045]	30/210 [435/3045]	80 [1160]	1:4,25 On request 1:8,1	1,9 [4,2]
FA2048	BDC1S35				350 [5075]	60/350 [870/5075]	135 [1960]		
FA2049	BDC2S21	SAE8	40 [10,6]		210 [3045]	30/210 [435/3045]	80 [1160]		1,83 [4]
FA2050	BDC2S35				350 [5075]	60/350 [870/5075]	135 [1960]		
FA2051	BDC3S21	SAE10	60 [15,9]		210 [3045]	30/210 [435/3045]	80 [1160]		2,1 [4,6]
FA2052	BDC3S35				350 [5075]	60/350 [870/5075]	135 [1960]		
Standard setting 350 bar [5075 PSI] **to 5 l/m** [1,32 USgpm]					**Standard setting 210 bar** [3045 PSI] **to 5 l/m** [1,32 USgpm]				

UPDATE. March 2023 (v.03)

Mineral oil: DIN 51524 ISO 6743/4 | **Oil viscosity**: 15 to 250 cSt 15-250 mm2/s | **Oil temperature**: -4°F + 176°F -20°C +80°C | **Ambient temperature**: -4°F + 122°F -20°C +50°C | **Max contamination index with filter**: 5 to 250 cSt 15-250 mm2/s | It is necessary a filter use to protect the valve (advised filtration 15 µm) | **Max leakage**: 0,25 cm3/min - 5 drops/min at 80% of the calibration pressure

Via Guadiana n° 8/1, 42124 Reggio Emilia - ITALY | www.fluid-app.it | **sales@fluid-app.it**

Fluid-app Srl reserves the right to modify its products without notice.
Fluid-app Srl si riserva il diritto di modificare i propri prodotti senza preavviso.