HYDAC OK 8S 4.6 B air-oil cooler

Manufacturer: HYDAC

Manufacturer part number / published order designation: 7706513

Published model: OK 8S 4.6 B

About this compilation

Prepared by Hydmaster from selected manufacturer documentation. Original technical pages follow without cropped drawings, rewritten data or altered units. This cover and index are Hydmaster editorial material, not a manufacturer-issued exact-execution datasheet.

Coverage: selected pages relevant to the identified size and configuration. Other options or neighbouring models retained on an original page apply only where explicitly identified.

Execution notes and conditions

Factory P/N and assigned B/X/IBP3/PRF configuration are proved by the exact current manufacturer card; selected family drawing does not print the P/N.

Drawing states consult factory for unlisted details. Exact execution general arrangement and configuration-specific thermal performance are not established by the family sheet.

Do not transfer alternate fan/AC/DC, optional filter or bypass components/overall dimensions into this factory execution. Curves remain applicable only under their printed test conditions.

Graph remains the original manufacturer family sheet with its printed caption and test conditions; it does not establish exact factory-P/N thermal performance.

Source-page index

Source page numbers below are physical pages of each complete original PDF. The original printed page labels and technical content remain unchanged. Compiled page numbers count this cover/index.

Source A: Hydac Ok Cooler Datasheets

Original pages	Compiled pages	Relevant content
4	2	Matching titleblock size-family installation drawing/ports and family operating limits; original optional configurations and graph retained with its printed caption/test conditions. Printed curve is not verified as this exact P/N performance.

REVISIONS					
ZONE	REV.	ECN	DESCRIPTION	DATE	APPROVED
	A		Production Release	3/24/2026	EJG/WJH

SPECIFICATIONS:


Materials	Housing: Welded Steel Heat Exchanger: Aluminum Heavy Duty Bar and Plate Fan: Plastic Motor: TEFC, NEMA
Mounting Orientation	Horizontal, motor shaft
Maximum Pressure	230 psi (16 Bar)
Fluids	Mineral oil to DIN 51524 Part 1 and 2, Water Glycol mixtures.
Ambient Temperature	50° – 104°F (10° – 40°C) (Contact factory for other temperatures)
Maximum Oil Viscosity	2000 cSt
Maximum Oil Temperature	266°F (130°C)
Standard Air Flow Direction	Air pulled across heat exchanger
Noise	86.7 dBa @ 1 Meter *


* Noise level is only a guide as acoustic properties depend on the characteristics of the room, connections, viscosity and resonance.

Fan Motor			
Specs		**Specs**	
Enclosure:	TEFC	**Insulation Class:**	F
Frame:	182TC	**Current @ Voltage:**	4.8 A @ 230 V
Frame Material:	Steel		
Power Output @ Frequency:	3.0 HP @ 60 HZ		4.2 A @ 460 V
Synchronous Speed @ Frequency:	1800 RPM @ 60 HZ	**Mounting Arrangement:**	F1
Voltage @ Frequency:	460 V @ 60 HZ	**Power Factor:**	90
	230 V @ 60 HZ	**Design Code:**	B
XP Class and Group:	None	**Agency Approvals:**	UL
XP Division:	Not Applicable		CE
Inverter Code:	Inverter Ready		CSA


Note: Hydac reserves the right to modify this information at anytime without prior notice.

OK 8S Performance Curves
Heat Dissipation @ ΔT = 40°F
Pressure Drop @ 20 cSt
(Tolerance: ± 5%)






NON BYPASS HYDRAULIC DIAGRAM




PRESSURE BYPASS HYDRAULIC DIAGRAM





TEMPERATURE PRESSURE BYPASS HYDRAULIC DIAGRAM

FAN ROTATION



AIR FLOW Standard **AIR FLOW Push**





Service Parts

ITEM NO.	DESCRIPTION	QTY.
10	Heat Exchanger or Bypass Heat Exchanger	1
20	Temp switch (AITR)	1
40	Housing	1
50	Fan	1
60	Fan Grill	1
70	E-Motor	1
90	BRACKET	2
	Optional Items	
220	IBP, or IBT Assembly	1
230	Air Filter	1

For Details not found in this document, consult the factory

UNCONTROLLED IF PRINTED

MATERIAL: -
FINISH: -
PROJECT:
Units: **INCHES**

DO NOT SCALE	NAME	DATE
DRAWN	EJG	01/13/2026
CHECKED	WJH	03/24/2026
APPROVED	WJH	03/24/2026

INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5
THIRD ANGLE PROJECTION

PROPRIETARY DRAWING - THIS DRAWING IS THE PROPERTY OF HYDAC INTERNATIONAL CORP. NO RIGHT OR LICENSE TO SUCH MATTER IS GIVEN OR WAVED BY SUPPLYING THIS DRAWING. IT IS NOT TO BE COPIED OR DISCLOSED OTHER THAN TO A GOVERNMENT AGENCY EXCEPT ON WRITTEN CONSENT OF HYDAC INTERNATIONAL CORP. IT MUST ALWAYS CONTAIN THIS NOTICE. THIS DRAWING CONTAINS CONFIDENTIAL INFORMATION BELONGING TO HYDAC INTERNATIONAL CORP. AND IS NOT TO BE USED TO ITS DETRIMENT." ANYONE FAILING TO COMPLY WITH THESE REGULATIONS, SHALL BE SUBJECT TO LEGAL ACTION.

HYDAC Cooling Division
Denver, NC USA

TITLE: OK 8S 4.6 DATASHEET

REF
SIZE D | DWG. NO. 7702104 | Revision A
SCALE: 1:8 | WEIGHT: 102 Kg | SHEET 1 OF 1