

Oleodinamica Marchesini V0282 VRAP 40/50 DE plough overturning valve

Manufacturer: Oleodinamica Marchesini
Manufacturer part number / published order designation: V0282
Published model: V0282

About this compilation

Prepared by Hydmaster from selected manufacturer documentation. Original technical pages follow without cropped drawings, rewritten data or altered units. This cover and index are Hydmaster editorial material, not a manufacturer-issued exact-execution datasheet.

Coverage: selected pages relevant to the identified size and configuration. Other options or neighbouring models retained on an original page apply only where explicitly identified.

Execution notes and conditions

Exact supplier-offered code, not a generated pressure-setting option.

Manufacturer photo represents the series.

No operating temperature range inferred from 50C curve conditions.


Source-page index

Source page numbers below are physical pages of each complete original PDF. The original printed page labels and technical content remain unchanged. Compiled page numbers count this cover/index.


Source A: Oleodinamica Marchesini VRAP DE technical datasheet

Original pages	Compiled pages	Relevant content
1	2	Complete applicable manufacturer article table, circuit, ratings, installation and dimensions

VALVOLE DI RIBALTAMENTO ARATRO A DOPPIO EFFETTO
DOUBLE ACTING PLOUGH OVERTURNING VALVES



SCHEMA IDRAULICO
HYDRAULIC DIAGRAM



IMPIEGO:
Valvola realizzata per l'impiego su cilindri per aratri reversibili, in modo da ottenere l'inversione automatica del flusso d'olio e quindi del moto del cilindro idraulico atto a portare in rotazione l'aratro. È dotata di una valvola di blocco a doppio effetto che fornisce una maggiore sicurezza e dà la possibilità di posizionare e bloccare il cilindro in qualsiasi punto. L'inversione di marcia dell'asta del pistone si effettua tramite una valvola di massima pressione compensata esattamente nel punto morto dell'aratro, sviluppando maggiore potenza e velocità. Questa valvola può essere montata anche su aratri pesanti e sbilanciati con cilindri aventi i seguenti diametri interni: 40/50, 60/80, 80/100, 100/110 e 110/130 mm.

MATERIALI E CARATTERISTICHE:
Corpo: acciaio zincato.
Componenti interni: acciaio temprato termicamente e rettificato.
Guarnizioni: BUNA N standard.
Tenuta: a cono guidato. Non ammette trafiletti.
Le valvole vengono fornite con pressione di scambio di circa 150 Bar: a seconda delle varie esigenze la pressione di scambio può essere variata agendo sul regolatore di pressione.


MONTAGGIO:
Collegare C1 allo stelo del cilindro, C2 al fondello e P e T alle prese macchina. Data la particolare configurazione, queste valvole possono essere montate in linea sul cilindro idraulico o fissate direttamente alla struttura dell'aratro tramite il foro filettato ricavato nel corpo.

USE AND OPERATION:
This valve has been designed for use on cylinders for reversible ploughs to obtain the automatic oil flow reversal, and therefore the reversal of the hydraulic cylinder which rotates the plough. It is provided with a double pilot operated check valve which provides leakage control for the cylinder in any position. The reversal of the cylinder is controlled by a pressure compensated relief valve set to exactly in the dead head point of the plough, generating more power and speed. It can be assembled on heavy and unbalanced ploughs with cylinders with the following internal diameters: 40/50, 60/80, 80/100, 100/110, 110/130 mm.

MATERIALS AND FEATURES:
Body: zinc-plated steel.
Internal parts: hardened and ground steel.
Seals: BUNA N standard.
Load holding: guided poppet, negligible leakage.
These valves are supplied with exchange pressure at about 150 Bar: according to your requirements, pressure setting can be modified by adjusting the pressure regulator.

CONNECTIONS:
Connect C1 to the cylinder's rod side, C2 to the head side, P and T to the machine's supply. Thanks to its shape, it can be assembled in-line on the hydraulic cylinder or directly fixed onto the plough by the threaded hole in the valve body.

CODICE CODE	SIGLA TYPE	PRESSIONE MASSIMA DI SCAMBIO MAX EXCHANGE PRESSURE Bar	PRESSIONE MAX MAX PRESSURE Bar
V0282	VRAP 40/50 DE	250	400
V0290	VRAP 60/80 DE	250	400
V0300	VRAP 80/100 DE	250	400
V0302	VRAP 100/110 DE	250	400
V0320	VRAP 110/130 DE	250	400



CODICE CODE	SIGLA TYPE	C2 P - T GAS	C1 mm	L mm	L1 mm	L2 mm	L3 mm	H mm	S mm	PESO WEIGHT Kg.
V0282	VRAP 40/50 DE	G 3/8"	Ø12	95	58	30	176	80	35	2,130
V0290	VRAP 60/80 DE	G 3/8"	Ø12	95	58	30	176	80	35	2,140
V0300	VRAP 80/100 DE	G 3/8"	Ø12	95	58	30	176	80	35	2,140
V0302	VRAP 100/110 DE	G 3/8"	Ø12	95	58	30	176	80	35	2,140
V0320	VRAP 110/130 DE	G 3/8"	Ø12	95	58	30	176	80	35	2,130