
TECH DATA

Single Counter Balance Valve Internal Vent

Part #	Ports	Pressure Range	Max Flow	Pilot Ratio	Material
VBCL3801S	3/8" BSPP	30-210 bar	40 L/min	4.25:1	Steel
VBCL3801S3	3/8" BSPP	30-210 bar	40 L/min	3:1	Steel
VBCL3801S8	3/8" BSPP	30-210 bar	40 L/min	8.75:1	Steel
VBCL3802S	3/8" BSPP	60-350 bar	40 L/min	4.25:1	Steel
VBCL3802S8	3/8" BSPP	60-350 bar	40 L/min	8.75:1	Steel
VBCL1201S	1/2" BSPP	30-210 bar	60 L/min	4.25:1	Steel
VBCL1201S3	1/2" BSPP	30-210 bar	60 L/min	3:1	Steel
VBCL1201S8	1/2" BSPP	30-210 bar	60 L/min	8.75:1	Steel
VBCL1202S	1/2" BSPP	60-350 bar	60 L/min	4.25:1	Steel
VBCL1202S3	1/2" BSPP	60-350 bar	60 L/min	3:1	Steel
VBCL1202S8	1/2" BSPP	60-350 bar	60 L/min	8.75:1	Steel
VBCL3402S	3/4" BSPP	60-350 bar	120 L/min	6.2:1	Steel






OLEOWEB MADE IN EUROPE

TECH DATA

Single Counter Balance Valve Internal Vent w/ External Pilot

Part #	Ports	Pressure Range	Max Flow	Pilot Ratio	Material
VBCR1401S	1/4" BSPP	30-210 bar	30 L/min	4.25:1	Steel
VBCR1401S8	1/4" BSPP	30-210 bar	30 L/min	8.75:1	Steel
VBCR1402S	1/4" BSPP	60-350 bar	30 L/min	4.25:1	Steel
VBCR1402S8	1/4" BSPP	60-350 bar	30 L/min	8.75:1	Steel
VBCR3801S	3/8" BSPP	30-210 bar	40 L/min	4.25:1	Steel
VBCR3801S8	3/8" BSPP	30-210 bar	40 L/min	8.75:1	Steel
VBCR3802S	3/8" BSPP	60-350 bar	40 L/min	4.25:1	Steel
VBCR3802S8	3/8" BSPP	60-350 bar	40 L/min	8.75:1	Steel
VBCR1201S	1/2" BSPP	30-210 bar	60 L/min	4.25:1	Steel
VBCR1201S8	1/2" BSPP	30-210 bar	60 L/min	8.75:1	Steel
VBCR1202S	1/2" BSPP	60-350 bar	60 L/min	4.25:1	Steel
VBCR1202S8	1/2" BSPP	60-350 bar	60 L/min	8.75:1	Steel





OLEOWEB MADE IN EUROPE

WARNING Hydraulic cylinders without a hose burst valve, pilot operated check valve or counter balance valve directly mounted to the cylinder will not meet Australian Standard AS1418.8, nor occupational health & safety rules.